## **CLARKE**®

### **NEW CLARKE ENGINE SERIES**

LISTED DIESEL FIRE PUMP DRIVERS

**1470-2100 RPM** | 460-800 BHP / *343-596 kW* 



## **NEW BASE ENGINE, SAME RELIABLE FIRE PROTECTION**

Clarke's C18H engine series utilizes the Cat® C18 twin turbo (TTA) base engine to provide best-in-class, fire pump drivers, engineered and assembled by Clarke. Drawing on 50+ years of experience in fire protection, Clarke provides superior engineering, standard 4 week lead times, competitive prices, and is backed by Clarke's global service dealer network.

The C18H engine series is UL1247 Listed and FM1333 Approved and designed in compliance with NFPA 20.



#### **SOFT START** Protects the engine and pump at start up by allowing the



#### **NEW DIGITAL DISPLAY**

Clearly displays the engine's operating conditions with intuitive graphics in multiple languages.



#### **HIGH EFFICIENCY COOLING SYSTEM** Minimizes raw water

flow, saving water and cost.



# **CLARKE**®

## **NEW CLARKE ENGINE SERIES**

LISTED DIESEL FIRE PUMP DRIVERS

**1470-2100 RPM** | 460-800 BHP / *343-596 kW* 

C18H0-	RATED SPEED BHP/kW				
SERIES	1470	1760	1900	2100	
UFAD18		460 / 343			
UFAD10			488 / 364	488 / 364	
UFAD28		510 / 380			
UFAD20			525 / <i>392</i>	525 / <i>392</i>	
UFAD38		542 / 404			
UFAD30			575 / 429	575 / 429	
UFAD48		600 / 447			
UFAD40			600 / 447	600 / 447	
UFAD58		650 / <i>485</i>			
UFAD50			650 / <i>485</i>	650 / <i>485</i>	
UFAD68		687 / 512			
UFAA78*	700 / 522				
UFAD78		700 / 522			
UFAD70			700 / 522	700 / 522	
UFAC18		755 / <i>563</i>			
UFAC10			755 <i>/ 563</i>	755 / <i>563</i>	
UFAC28		800 / 596.5			
UFAC20			800 / 596.5	800 / 596.5	

OVERALL DIMENSIONS - IN. (MM)
66.1(1678) H × 79.6(2022) L × 45.2(1147) W

MODEL NOMENCLATURE (11 Digit Models)

C18H0-UFAD78

Base Engine
18 Liter
18 Liter
19 Liter

FM

APPROVED

\*C18H0-UFAA78 is non-emissionized and available for export only

WHY CHOOSE CLARKE?						
FEATURES & BENEFITS	CLARKE	COMPETITORS				
4 Week Lead Time Standard (Quick Ship Available)		A	В			
	<b>V</b>					
Standard Three Year Warranty*	✓					
Access to Global Clarke and Cat Service Network	✓					
Cooling System; Optimizes Raw Water Flow	✓					
Soft Start for Commissioning	✓	✓				
1 and 2 Year Maintenance Kits	✓					
Optional - Crankcase Ventilation System	✓					
Optional - Pump Ready Base	✓	✓				
Optional - Driveshaft and/or Torsional Coupling	✓	✓				
Optional - Tropicalization Package	✓					
Optional - Two Stage Air Cleaner	✓	✓	✓			
Optional - Sound Attenuated Engine Only Enclosure	✓	✓				
COMING SOON - Clarke Patented PLD PLD	✓					

For more information and technical data, please reference our complete specification sheet (C137765) and installation drawings (D844, D845, D846) \*Standard three year warranty available for NEW C18H installations when serviced with Clarke Maintenance Kits.

